

DTF-T30

DIRECT TO FILM PRINTER



Self-development



long life



High precision



low cost

TECHNICAL PARAMETER

Model	DTF-T30
Printhead	2*Epson I1600-A1
Printing Color	CMYK+W
Printing Size	300mm
Printing Speed	720*900DPI 6PASS 4m ² /h 720*1200DPI 8PASS 3m ² /h 720*1800DPI 12PASS 2m ² /h
RIP Software	RIIN/Flexiprint/CADlink/Maintop/NeoStampa
Media Transfer	Auto feeding and take-up system
Heating Method	Front and back independent heating
Ink System	Auto ink supply, white ink circulating and stirring
One click drying	Auto-drying function after printing
Powder shaker linkage intelligent protection	Powder shaker will be in standby mode to save energy
Power Supply	110V/220V 50~60HZ 200W/1500W
Work Environment	Temperature:20°C~30°C Humidity:35%~65%
Machine Size/Weight	Printer: 1168*884*1218mm 120kg Powder Shaker: 640*932*573mm 45kg
Packaging Size/Weight	Printer: 1580*870*740mm 137kg Powder Shaker: 800*600*720mm 56kg



CMYK+W



2/3*Epson I1600-A1



Temperature control



Anti-collision system